


FOOT VALVE Cast Iron

Model : FCC



Materials

NO.	Partname	Material
1	Body	Cast Iron
2	Disc	Cast Iron
3	Guide	Cast Iron
4	Seal	NBR
5	Spring	SUS 304
6	Strainer	Galvanized steel / SUS304
7	Seat	Brass
8	Screw	Steel

Pressure - Temperature ratings

Working Pressure : 10 Bar
 Test Pressure : 16 Bar
 Service Temperature : 80° C

Technical Features

- Operates in any position from horizontal to vertical ascending or oblique pipeline to allow flow in one direction.
- Minimum head loss. Silent, reliable sealing and various type available NBR/EPDM/VITON/PTFE
- Simple and robust - design suitable for general applications. Dose not generate hammering.

Dimension

mm

Size		H	D	F
MM.	INCH			
50	2	143	165	97
65	2 1/2	185	185	125
80	3	218	200	150
100	4	265	220	181
125	5	333	254	217
150	6	373	285	256
200	8	483	343	336
250	10	572	406	416
300	12	652	482	486

NO. HOLE of Flange

ANSI 150	JIS 10K	PN10
4	4	4
4	4	4
4	4	8
8	8	8
8	8	8
8	8	8
8	12	8
12	12	12
12	16	12