

DUO CHECK VALVE *Stainless*

Model : DD-8



Materials

NO.	Partname	Material
1	Body	CF8 / CF8M
2	Plate	CF8
3	Spring	Stainless 304
4	Hinge Pin	Stainless 304
5	Plug	CS
6	Body Bushing	PTFE
7	Spring Bushing	PTFE
8	Stop Pin	Stainless 304
9	Eye Bolt	SS304 (8")
10	Body seat	EPDM / NBR / VITON

Features

- Water type connection
- The valve are designed to prevent reverse flow automatically
- Wafer Type
- Note :
- Can be adapted for different connection : PN10/16 ANSI125/150 ,JIS10K

Test Requirements

Working Pressure : 150PSI (10 bar)
 Maximum Pressure : 299PSI (14 bar)
 Shell test Pressure : 300PSI (21 bar)
 Maximum temperature : -30° C -150° C

Dimension

mm

Size	IN	DN	B	E	A		
					PN10/16	150P	10K
2	50	43	65	107	102	101	
2 1/2	65	46	80	127	121	121	
3	80	64	94	142	133	131	
4	100	64	117	162	171	156	
5	125	70	145	192	193	187	
6	150	76	170	218	219	217	
8	200	89	224	273	276	267	
10	250	114	165	328	336	330	
12	300	114	310	378/382	406	375	
14	350	127	360	438/442	448	420	
16	400	140	410	488/495	511	483	
18	450	152	450	538/555	546	538	
20	500	152	505	592/617	603	593	
24	600	178	624	695/734	714	697	

